

Length Overall Including bow rail & swim platform	47'-5"	Overall Height Measured to outriggers in up position	31'-5"
Beam Including gunwales	15'-0"	Dry Weight Measured ISO 8666	31,300 lbs
Draft Waterline to propellers (depends on lo	3'-11" ad)	Tank Capacities	
Overall Height Measured to center outrigger	19'-6"	Fuel Tank Capacity Water Tank Capacity Holding Tank Capacity	528 gallons 120 gallons 40 gallons

ENGINES

- Twin Volvo IPS 600 (320kw/435 hp) with IPS propulsion units, electronic variable rate steering and electronic controls including joystick for slow speed maneuverability.
- ** Upgrade ** Volvo Digital Positioning system (DPS)
- ** Upgrade ** Cockpit Joystick Mounted onto GRP Part with canvas cover
- Product Designation D6-435D-F (IPS)
- Product Number 40869406
- Port Engine Serial Number #A694915
- Starboard Engine Serial Number #A711550
- Port Transmission Serial Number #3940017277
- Starboard Transmission Serial Number #3940017278

VESSEL STABILIZATION

 ** Upgrade ** Sea Keeper 5 (model #SK5000) anti-roll control gyro stabilizer

SOUTH FLORIDA TROPICAL PACKAGE

- ** Upgrade ** Generator upgrade to Onan model #MDKDN-1726266 13.5kW/60Hz/1800rpm. Generator Serial Number #D170169994
- ** Upgrade ** Tropical package Air-conditioning, Saloon (36,000BTU), Flybridge (24,000BTU), Fwd stateroom (12,000BTU), Aft stateroom (12,000BTU).
- ** Upgrade ** Factory tinted glass for saloon windows front & sides for heat reflection.

ELECTRONICS / NAVIGATION

- Volvo Glass Bridge: 7-inch multi-function display
- Chart Plotter: (2) Garmin 7612 including GPS & GRID controller
- Auto Pilot: Volvo/Garmin Auto Pilot integrated into Glass Bridge
- **Radar**: Garmin 4KW GMR424XHD2 Open Array Radar 5" Seaview mount
- **Depth Sounder**: Garmin GSD 24 Sounder with 1kW depth/temp transducer
- VHF Radio: Icom IC-423G VHF radio
- **Camera**: Garmin IRIS 65 Micro Dome in engine room
- SPOT Trace: GPS tracking system

COCKPIT

- ** Upgrade ** BBQ console combining electric BBQ, sink with faucet, large storage area, enclosed garbage bin and solid surface benchtop
- ** Upgrade ** Padded bolster fiiter to cockpit coaming
- ** Upgrade **Rod holders (12X) to flybridge rail
- Access ladder with teak treads to flybridge
- Aft facing lounge on mezzanine level with drawers underneath for storage
- Cockpit floor reinforced with alloy plate for chair or table
- ** Upgrade ** 4-inch stainless steel post with spider mount for Pompanette 4-rod, two-drink holder rocket launcher with drawer compartment and protective canvas cover.
- ** Upgrade ** Fiberglass oval table with four cup holders and spider mount for 4-inch base.



- Cockpit hatches with heavy-duty stainless steel lock downs with gas struts
- Double action manual emergency bilge pump for engine room
- Engine room access (lockable)
- Fish bins x 2 (nonremovable) in cockpit floor with Whale Gulper 320 discharge pumps.
- ** Upgrade ** one fish bin converted to live recirculating bait well
- Grab rails to assist access to side decks
- ** Upgrade ** Triangular quarter strataglass to cockpit port & starboard with additional grab rails.
- Handheld shower with hot & cold fresh water
- Lighting spotlights, overhead and courtesy (DC) LED
- Lockers (GRP) for cockpit storage
- Self-draining cockpit to the stern
- Stainless steel rear bulkhead incorporating sliding saloon door and opening up rear window with gas strut and lock
- Steps to side deck port & starboard
- Top loading, freezer box to port at flybridge ladder
- ** Upgrade ** Upsized compressor and freezer plates installed within cockpit freezer box.
 Isotherm model #U400X133P12111AA. Serial number i#2330 8752.
- Transom door GRP opening outwards with lift up bridge
- Wash down tap (fresh water) powered by Jabsco Par-Max 5.0 pump model #37100-0394 (24V)
- Wash down tap (sea water) powered by Jabsco Par-Max 5.0 pump model #37100-0394 (24V)
- ** Upgrade ** Rupp 32-foot double spreader aluminum outriggers with triple rigging
- ** Upgrade ** Rupp center outrigger
- ** Upgrade ** 10 Screwless Rod holders with backing plates installed in gunwale
- ** Upgrade ** port and starboard Hubbell 15amp electrical connections for 12V for deep drop fishing.

CONSTRUCTION

- Hand laid, molded fiberglass hull, cored deck and flybridge
- Independent compartments throughout hull
- Isophthalic gelcoat exterior (white)
- Solid GRP chines and hull bottom
- Vinylester resin in first outer layer of hull

• Watertight collision bulkhead forward

DECK

- Lewmar Delta Anchor 20kg (45lb), 70m (230ft) of 8mm (5/16-inch) galvanized short link chain
- ** Upgrade ** spare anchor
- Anchor chain chafe plate fitted to bow sprit
- Anchor locker with rope/chain divider (offset to stbd). Access from hatch on deck
- Anchor safety strap
- Muir anchor windlass model #AA560 vertical with overload protection circuit breaker, suit rope & chain, up & down switches & remote to helm
- Bow rail welded stainless steel (316 marine grade, highly polished) with mid safety wire including flag staff and burgee (bow flag)
- Bow roller stainless steel self-loading through bowsprit, heavy duty
- Cleats stainless steel 11 (x 8) 12 (x 2) fairleads aft corners (x 2) pop up cleats (x 2) for fenders
- Deck hatches x3 (lockable)
- Fender holders (x 2) to bow rail
- Rails port & starboard of flybridge above window for safe passage to forward deck
- Rub rail impact and UV resistant PVC (white) with stainless steel insert strip
- Sea water wash down tap at anchor locker
- ** Upgrade ** Underwater Lighting (3 x Transom Lights) Lumitec SeaBlaze X Blue/White

ELECTRICAL

- Alternators Port alternator charges port start bank and auxiliary bank via a Voltage Sensitive Relay (VSR). Starboard alternator charges starboard start bank and designated alternator charges the house bank
- Batteries (maintenance free) Independent port & stbd start (totalx4), house (x2) and auxiliary (x2)
- Battery banks individually isolated
- Battery charger -automatic (80amp/24VDC) to house bank
- Battery paralleling system for emergency engine start
- Bonding system, to all metallic hull fittings under the water line with zinc anode including galvanic isolator
- Digital DC circuit control and protection
 incorporating 'intelligent' operation with user

Hull ID #RIY430631718



programmable usage modes, timer circuits, light dimming and circuit bypass, operational via conventional switches, signal set points as well as LCD display modules.

- C-Zone Digital monitoring system including AC and DC power metering, fluid tank level monitoring and DC circuit status via illuminated color digital touchscreen display, 1x at helm & 1x saloon control panel area
- Engine monitoring including instrumentation, alarms and hour meters
- Inverter to power televisions (as fitted)
- Navigation lights LED (international standard)
- Wiring coded, numbered & assembled in looms where possible
- ** Upgrade ** Independent 24V to 12V 60-amp continuous load transformers for port and starboard electrical connections in cockpit

ELECTRICAL - AUDIO/VISUAL

- ** Upgrade ** Starlink satellite Internet system.
- Flybridge AM/FM stereo CD player and iPod connectivity (head unit to helm) Including 2x speakers
- Saloon Fusion model #MS-AV755 AM/FM Stereo with Satellite Radio, CD/DVD player and iPod interface, amplifier, 4 speakers plus subwoofer to saloon, 2 speakers and remote to cockpit
- Saloon 32-inch Samsung LED Smart TV integrated into saloon with manual fold up mechanism
- ** Upgrade ** Saloon: Apple TV
- ** Upgrade ** Master Stateroom GPX 22-inch LED TV/DVD/12V
- ** Upgrade ** Aft Stateroom GPX 22-inch LED TV/DVD/12V

FLYBRIDGE

- Drink holders in helm console
- Ergonomically designed helm console
- Hardtop GRP, on stainless steel supports, inc. spotlight with remote, opening hatch, grab rail and overhead lighting
- Lounge seating forward (white vinyl) with storage underneath
- ** Upgrade ** upholstery upgrades for lounge seating
- Overhead and courtesy lights (DC) LED
- Rails on rear of flybridge including midrail

- Storage lockers (GRP)
- Table (GRP) with solid surface infill including drink holders fitted on a stainless steel pedestal
- Wet bar including, locker, grab rail, garbage bin, solid surface bench top, sink and mixer tap
- ** Upgrade ** Refrigerator underneath wet bar. Vitifrigo model #C621XOCX. Serial #171103323.
- Wrap around front windshield/deflector
- ** Upgrade ** Snap down carpet in flybridge

GENERAL SPECIFICATIONS

- All stainless-steel exterior fastenings 316 marine grade
- All stainless-steel mirror finish with ground welds
- Antifouling: 2 coats epoxy undercoat, 2 coats antifoul with Propspeed coating to propellers & Pod Drive gear
- Fenders x 4, dock lines x 4 and boat hook
- Fire extinguishers, portable x 4
- Gelcoat 1 litre, shipped on board
- Hull colour white (gelcoat) with black antifouling
- Owner's manual high quality and comprehensive
- Safety labels English language

HEAD – DAY

- Contemporary design solid surface vanity benchtop with porcelain bowl and quality mixer tap
- Exhaust Fan
- Flooring in high quality vinyl
- Hatch white with screen & blind
- Lighting, overhead (DC) LED
- Private entrance door
- Shower stall with frameless glass door, shower head (on slide bar) and automatic sump pump
- Toilet roll holder & other bathroom accessories
- Wall mounted Towel holders
- Under bench storage
- Dometic (Sealand) 24V Vacuflush #506 toilet (fresh water)
- Holding tank level indicator lights
- Vanity cabinet with mirror

HEAD – MASTER

- Contemporary design solid surface vanity benchtop porcelain bowl and quality mixer tap
- Exhaust Fan





- Flooring in high quality vinyl (excluding shower)
- Holding tank level indicator
- Lighting, overhead (DC) LED
- Mirror
- Private entrance door
- Shower stall with glass partition, frameless glass door, automatic sump pump and shower head (on slide bar)
- Toilet roll holder & other bathroom accessories
- Wall mounted Towel holders
- Dometic (Sealand) 24V Vacuflush toilet (fresh water)
- Vanity cabinet

HELM

- Chain counter (anchor)
- Ritchie compass, 4.75 with light
- Dash cover (white)
- Electronic engine control unit
- Ergonomically designed aft helm position, with drink holders and comprehensive electronic engine instrumentation
- Pompanette Helm chair covers (x2) (white)
- Helm electronics area with 24VDC feed, main circuit breaker protected
- Safety monitoring panel for bilge pumps, sump pump, navigation lights, engine room lights and high water alarm
- Steering wheel stainless steel
- VHF radio including aerial antenna

MECHANICAL

- ** Upgrade ** Reverso #GP-703-24 3-valve manifold oil changing system to main engines and genset
- ** Upgrade ** Reverso fuel polishing system in engine room
- Acoustic & thermal insulation to engine room
- All through hull fittings on or below the water line fitted with ball valves, all hoses double clamped
- Bilge pumps auto & manual override x 2
- Engine access via large hatch in cockpit floor. (Opens remotely by use of an electric actuator). Day access through smaller hatch with gas struts
- Engine monitoring display (Volvo) 7-inch Glass
- Engine mounts anti vibration
- Engine room lighting AC and DC
- Engine room Delta "T" Systems 24V blower fans
- External & internal seawater strainers to main

raw water intakes - generator & air conditioning (engines through IPS system)

- · Fiberglass aqualift exhaust system for generator
- Fire suppression system for engine room with automatic/manual controls.
- Kuuma Innovations model #11840 stainless steel hot water heater for freshwater system (replaced 2024).
- Fresh water system (pressurized) with dual water tanks, total capacity of 122 US gallons with water fills on both starboard and port sides.
- ** Upgrade ** Fresh water pump, Secondary backup pump (switched independently)
- Fresh water tap & hose set in engine room
- Fuel filters/ water separator for engines & generator
- ** Upgrade ** Dual Racor fuel filters/ water separator for main engines
- Fuel lines all swaged with fuel fills on both starboard and port sides.
- Fuel shut-off valves with access that is remote from engine room
- Fuel tank, GRP coated in fire retardant flocoat, (528 US gallons)
- Holding tank capacity (40 US gallons)
- Props IPS twin nibral 3 blade (counter rotating)
- Propspeed coating to propellers
- Steering at low speed via Volvo IPS joystick docking control
- Trim Tabs Electric / Hydraulic
- Vacuflush sanitation system with switch at helm for overboard pump out and deck fitting for dockside pump out
- Volvo active corrosion protection (ACP) system (Volvo IPS only)
- Volvo Line cutters between props
- Volvo Penta IPS propulsion units (x2)

REGIONAL SPECIFICATION AMERICAS

- AC power outets (doubles) to all staterooms, heads, galley, saloon, flybridge, cockpit and engine room
- Outlets with Ground Fault Circuit Interrupter
 (GFCI) protection
- Shore power electrical inlet 50 Amp
- Shore power lead
- Vessel AC system built to 110V/60Hz

SALOON

• Air conditioning: 16,000 BTU reverse cycle to



heat or cool

- C-Zone Display interface with safety monitoring alarms and information
- Folding saloon table with adjustable height pedestal
- ** Upgrade ** Convertible dinette table, Manual hi/lo table drops down to become additional berth. Does not include mattress infill.
- Galley Breakfast Bar forward with 2x removable bar stools
- Polished stainless steel handrail recessed into padded headliner
- Liquor cabinet with timber benchtop and bottle/glass storage
- ** Upgrade ** Riviera bar accessory package
- Lounge, U shape in premium leather with storage underneath
- Rod storage locker in headliner. Electric open/close
- ** Upgrade ** Fishing Rod storage racks within saloon overhead compartment
- Upper pelmets
- Lighting, overhead (DC) LED
- Liquor Cabinet
- U-Line refrigerator/ Icemaker combination. Model #ULN-C029B-03A. Serial #1641871-02-0005.
- ** Upgrade ** Exterior mounted screen window cover (black breezeway) for front and side windows.

SALOON - GALLEY

- Aft galley arrangement
- Electric cooktop, dual element with removable pot keepers. Whale (Attwood) model #G2247-5100. Serial #012517751.
- Dometic 24V cooking exhaust fan with light
- · Flooring in commercial grade vinyl
- Garbage bin with concealed cover
- Overhead LED lighting
- Microwave/convection oven. Frigidaire model #FFTC1278LS. Serial number #1G64905428.
- Undercounter Vitrifrigo 2-drawer refrigerator freezer. Model #DW180IXD4-EF-2 and serial number#002303001981.
- Solid surface benchtop including stainless steel sink with mixer tap
- Storage cabinets & drawers with soft close runners
- ** Upgrade ** Riviera dinnerware

STATEROOM – AFT

- Berth single along outboard hull side
- Berths 2 x fixed single athwartships including storage underneath
- ** Upgrade ** two twin berth slide to form a queen size berth. Linens included for both two twins and queen size berths.
- · Blinds fitted to port holes and hull windows
- · Carpet with underlay
- Door 2 way, allows the conversion of day head into a private ensuite or allows day head access with aft cabin privacy
- Drawer cabinet with soft closing runners
- Feature bulkheads upholstered
- Hanging locker with cedar lining and auto lighting (LED)
- Large, fixed hull windows port and starboard with tinted tempered glass
- Large framed feature mirrors fitted to aft bulkhead
- Reading and overhead lighting (DC) LED

STATEROOM - FORWARD VIP

- Access to private ensuite
- Carpet with underlay
- Feature bulkheads upholstered
- Hatch white with screen and blind
- Headboard upholstered
- Hull and head linings, vinyl covered with padding
- Master berth with under bunk drawers and side tables
- Porthole fixed bonded glass recessed into hull sides with fitted window furnishings
- Private entrance door
- Queen walk-around berth with innerspring mattress
- Reading and overhead lighting (DC) LED
- Robe with hanging rail to starboard, cedar lined with auto lighting (DC) LED
- Robe with shelves to port, cedar lined with auto lighting (DC) LED
- Storage cabinets outboard with mirrored doors and positive locking hardware

TIMBER FITOUT

- Cherrywood interior with high gloss varnish throughout
- Commercial grade flooring to galley (Kentucky Oak)



PERFORMANCE CHART BASED ON SEA TRIAL

	RPM's	Load	Turbo	Speed (mph)	Fuel (mpg)
Starboard	3500	100%	27 psi	31.4 mph	0.7 mpg
Port	3490	100%	27 psi		
Starboard	3000	83%	22 psi	23.6 mph	0.7 mpg
Port	3000	82%	21 psi		
Starboard	2900	78%	20 psi	22.5 mph	0.7 mpg
Port	2900	77%	20 psi		
Starboard	2800	81%	17 psi	21.2 mph	0.7 mpg
Port	2800	79%	17 psi		
Starboard	2600	85%	14 psi	18.0 mph	0.7 mpg
Port	2600	84%	14 psi		
Starboard	2400	84%	11 psi	14.7 mph	0.7 mpg
Port	2400	82%	11 psi		
Starboard	2200	91%	7.8 psi	12.7 mph	0.8 mpg
Port	2200	90%	7.5 psi		
Starboard	2000	78%	4.3 psi	11.8 mph	0.9 mpg
Port	2000	77%	4.3 psi		
Starboard	1800	65%	2.6 psi	10.9 mph	1.2 mpg
Port	1800	64%	2.6 psi		
Starboard	1600	59%	1.5 psi	10.1 mph	1.5 mpg
Port	1600	61%	1.5 psi		
Starboard	1400	50%	0.9 psi	9.0 mph	2.0 mpg
Port	1400	51%	0.6 psi		